

## CHRYSO® EnviroMix® 330

Full Range Water Reducing Admixtures

### DESCRIPTION

CHRYSO® EnviroMix® 330 provides high early strengths to increase SCM content in concrete and achieve substantial savings. It provides optimized workability and placeability to achieve targeted concrete quality and performance on-site while reducing jobsite time and costs.

Meets or exceeds the requirements of ASTM C-494 Type A and F

### ADVANTAGES

- Allows better utilization of mixes incorporating high volumes of pozzolans such as fly ash
- Proprietary finishing aid improves workability and finishability
- High Early Strength
- Reduces cracking and shrinkage
- Improves Cementitious Material Performance (More PSI/lb)
- High SCM usage contributes to the protection of our environment (Reduction of CO<sub>2</sub> emissions encouraged by LEED directives)

### FIELDS OF APPLICATION

- All Cement Types
- Ready Mix Concrete
- Manufactured Sand
- Concrete Paving

### Method of Use

#### Dosage

- The recommended dosage rate for CHRYSO® EnviroMix® 330 is 3 to 10 oz/cwt (195 to 652 ml/100 kg) of cementitious material for a Type A and 7 to 18 oz/cwt (456 to 1174 ml/100 kg) of cementitious material for a Type F.
- CHRYSO® EnviroMix® 330 can be added with the initial water or, for optimum performance, on the wetted concrete. It should not be added with or on the dry cement.
- Dosage rates may vary when used in conjunction with other CHRYSO admixtures.
- Trial mixes should be conducted to determine the dosage rate needed.
- Because local job conditions vary, please contact your local CHRYSO sales representative for further assistance if using the product outside the recommended dosage ranges.

### CHARACTERISTICS

Product Nature	Liquid
Color	Amber-Brown

### PRECAUTIONS

- CHRYSO® EnviroMix® 330 should be stored at or above 34°F (1°C). If frozen, thaw and agitate thoroughly to return to its normal state before use.

The information contained in this technical data sheet is given to the best of our knowledge and the result from extensive testing - which were conducted in order to remain as objective as possible. However, it cannot, in any case, be considered as a warranty involving our liability in case of misuse or any different use of our products, other than those from the "Application" paragraph of this technical data sheet. Some application tests should be carried out before using the product to ensure that the methods of use and conditions of application of the product are satisfactory. Our technical assistance is at the disposal of the users. [www.chryso.com](http://www.chryso.com)

CHRYSO Inc. - 3958 Ruger Dr • Royse City • TX 75189 & PO Box 190 • Rockwall • TX 75087 Tél.:+1 (972) 772 6010

## TECHNICAL DATA SHEET

# CHRYSO® EnviroMix® 330

Full Range Water Reducing Admixtures

Chryso  
Concrete  
Solutions

12/11/2024

Shelf life	12 months
Cl <sup>-</sup> ions content	< 0,100 %
Specific gravity (25°C) in g/ml	1,050 ± 0,000
pH (25°C)	5,00

This product does not contain any purposely added calcium chloride or other chloride based components. It will not promote or contribute to corrosion of reinforcing steel in concrete.

- Do not use pressurized air for agitation.
- CHRYSO® EnviroMix® 330 is compatible with most CHRYSO admixtures if added separately to the concrete mix.
- However, it is not recommended for use in concrete containing naphthalene-based admixtures including ProPel AG, or melamine-based admixtures.

## SAFETY

Prior to any use, please read carefully the Safety data Sheet.

## PACKAGING

- 55 gallon drum
- 275 gallon tote
- Bulk

The information contained in this technical data sheet is given to the best of our knowledge and the result from extensive testing - which were conducted in order to remain as objective as possible. However, it cannot, in any case, be considered as a warranty involving our liability in case of misuse or any different use of our products, other than those from the "Application" paragraph of this technical data sheet. Some application tests should be carried out before using the product to ensure that the methods of use and conditions of application of the product are satisfactory. Our technical assistance is at the disposal of the users. [www.chryso.com](http://www.chryso.com)

CHRYSO Inc. - 3958 Ruger Dr • Royse City • TX 75189 & PO Box 190 • Rockwall • TX 75087 Tél.:+1 (972) 772 6010